

## PRODUCT SHEET

# **REXNORD<sup>®</sup> 6997 SERIES** MATTOP<sup>®</sup> CHAIN STRONGER FOR LONGER CONVEYOR

RUNS AND LONGER LIFE IN PWC TUNNEL APPLICATIONS

Regal Rexnord continuously develops innovative conveyor chain, and chain material solutions to meet the increasing performance demands of the Pasteurizer, Warmer and Cooler (PWC) tunnels for customers in the Food and Beverage industries.

The Rexnord 6997 Series MatTop Chain is a stronger and stiffer upgrade from the Rexnord 5997 Series, offering improved container stability and chain performance while delivering ease of installation and maintenance to customers.

### **FIFTEEN PERCENT STRONGER**

The 6997 Series MatTop Chain offers improved strength for longer conveyors and longer life. Compared to the Rexnord 5997 Series MatTop Chain, the 6997 is 15% stronger.

### **IMPROVED PRODUCT STABILITY AND CHAIN PERFORMANCE**

The design of the Rexnord 6997 Series MatTop Chain offers:

- Improved container stability at transfers leading to less product damage and loss
- Improved lateral stiffness for fewer downed containers
- Straight line ribs for better product handling

### SUPERIOR CHAIN MATERIAL

Regal Rexnord, with a long history of providing superior performance materials offers USP material for the Rexnord 6997 Series MatTop Chain. The USP is polypropylene plus stabilizing antioxidant additives. USP is specifically formulated to withstand chemically aggressive PWC tunnel applications.

### EASY RETROFIT FROM 5997 TO 6997

The 6997 Series utilizes the same conveyor structure, sprockets, transfer combs and DTS-C as the as the 5997 Series MatTop Chain for an easy retrofit.

### **ADDITIONAL BENEFITS**

- Handles wide range of temperature variation
- Smooth and stable 90° transfers at both infeed and discharge
- High strength, product stability, and chemical resistance

- Metal Cans **Glass Bottles** - Rigid PET

**KEY INDUSTRY** 

Food

Beverage

- Sauces
- Oils - Pickled Goods

### **KEY APPLICATIONS**

• Pasteurizer, Warmer and Cooler (PWC) Tunnels

### **GENERAL** SPECIFICATIONS

- Pitch: 2.25 inch (57, 15 mm)
- Open area: 29%
- Height: 0.97 inch (24, 6 mm)

### **QUESTIONS?**

**Contact the Application Engineering team at:** 

FlatTop.Tech.Support@ regalrexnord.com





## **REXNORD<sup>®</sup> 6997 SERIES MATTOP<sup>®</sup> CHAIN**

### SPECIFICATIONS

Available Widths	Available Materials	Temperate Range USP Material								_			
		Fahrenheit			Celsius			Working Load		Approximate Weight		Backflex Radius	
		min	max		min	max							
			dry	wet		dry	wet	lbs/ft	N/m	lbs/ft^2	kg/m^2	mm	inch
18 in (457,2 mm) with increments of 6 in (152,4 mm)	USP	40°F	220°F	212°F	4°C	104°C	100°C	2700	39393	2.62	12.8	90	3.5

Direction of Tra

### **GENERAL INFORMATION:**

- Runs on Rexnord 5996 Series Sprockets
- Uses polypropylene rods
- TwistLock<sup>™</sup> plugs on both sides of the chain

### **LEARN MORE**



### **Superior Product Handling**

Improved lateral stiffness allows for fewer downed containers. The straight line ribs allow for better product handling.

### **USP** Material

USP offers superior resistance to chemicals used in cleaning and boil-out as well as extended chain life in hightemperature environments.

### Sprocket Pocket Spacing

Contains uniform sprocket positioning across the bottom of the chain, for standard widths. Centerline is 1.5 inches to the first sprocket pocket, then 3 inches for the rest.

### **Proven Pin Retention**

TwistLock plugs on both sides of the chain allow better access to the rods to make the assembly and disassembly processes quick and easy.



### Automation and Motion Control Regal Rexnord


Contact us: rexnord.com/contact

regalrexnord.com

The proper selection and application of products and components, including assuring that the product is safe for its intended use, are the responsibility of the customer. To view our Application Considerations, please visit <a href="https://www.regalrexnord.com/Application-Considerations">https://www.regalrexnord.com/Application-Considerations</a>. To view our Standard Terms and Conditions of Sale, please visit <a href="https://www.regalrexnord.com/Terms-and-Conditions-of-Sale">https://www.regalrexnord.com/Terms-and-Conditions-of-Sale</a> (which may redirect to other website locations based on product family).

"Regal Rexnord" is not indicative of legal entity. Refer to product purchase documentation for the applicable legal entity. Regal Rexnord, Rexnord, MatTop and TwistLock are trademarks of Regal Rexnord Corporation or one of its affiliated companies © 2021, 2023 Regal Rexnord Corporation, All Rights Reserved. MCSSP23050E • Form# FT5-148E

### 3.5 [85] Barkifley Radius



[18.237] ain Height

[24.587

# fr**, Regal**Rexnord